Fact Sheet



iL F3000

Precise weighing, easier cleaning - benefit from the new generation of Bizerba load receptors. With its open design, the iL F3000 series is extremely robust while ensuring good accessibility. Thanks to its easy-to-clean design and optional hinged load platters, you can use the load receptors even in hygienically critical environments.




More information High performance with a wide range of solutions and options.

Specifications	Facts	Details
Weighing range	From 300 kg to 3000 kg	Metrologically approved interval from 100 g - 1000 g
Load receptor dimensions	800 x 600 mm	
	800 x 800 mm	
	1000 x 800 mm	
	1000 x 1000 mm	
	1250 x 1000 mm	
	1500 x 1250 mm	
	1500 x 1500 mm	
Overall height	85 mm	Level adjustment by means of feet screws, approx. + 5 mm
Materials	V2A stainless steel	Load frame and load platter in different versions
	Stainless steel V2A checkered plate	
	Steel lacquered	
Load cells	HLC	3000e, 6000e or 2x3000e, dual-range scale
	SB4	3000e or 2x3000e, dual intervale scale
		Up to 30.000d (not verifiable)
	HLC - load cell nominal load 550 kg	Design load 1: 2000 kg
		Design load 2: 1400 kg
		Design load 3: 950 kg
		Wheel load: 300 kg
		Axle load: 600 kg
	SB4 - load cell nominal load 510 kg	Design load 1: 1800 kg
		Design load 2: 1400 kg
		Design load 3: 950 kg
		Wheel load: 300 kg
		Axle load: 600 kg
	HLC - load cell nominal load 1100 kg	Design load 1: 4000 kg
		Design load 2: 2800 kg
		Design load 3: 2000 kg
		Wheel load: 600 kg
		Axle load: 1200 kg


	SB4 - load cell nominal load 1020 kg	Design load 1: 3600 kg
		Design load 2: 2800 kg
		Design load 3: 2000 kg
		Wheel load : 600 kg
		Axle load : 1200 kg
	SB4 - load cell nominal load 2020 kg	Design load 1: 6000 kg
		Design load 2: 4500 kg
		Design load 3: 3000 kg
		Wheel load: 1000 kg
		Axle load: 2000 kg
Installation type	Free-standing with or without drive-on ramp(s)	
	Built-in in scale pit	
IP rating according to EN 60529	IP68	Cable junction box
	IP68 / IP69	Load cells
Explosion proof version	Zone 1/21	Load cells in Ex ib version for Ex zones and 21
		Additional plate for Ex zones 2 and 22
	Zone 2/22	
Options	Facts	Details
Load platter versions	Screwed	onto load frame
	Removable / multi-sectional	2 or 3-sectional
	Hinged 1 part	with gas pressure spring
	Hinged 2 parts	with gas pressure spring

Info graphics

Symbols



Dimensional drawings



HF_iL F3000_V2_EN Subject to technical modifications Page 2 / 3

Bizerba SE & Co. KG

Wilhelm-Kraut-Straße 65 72336 Balingen

T +49 7433 12-0 fax: +49 7433 12-2696 marketing@bizerba.com

www.bizerba.com

HF_iL F3000_V2_EN Subject to technical modifications Page 3 / 3