

Data Sheet

BIZERBA

iL Special 4000D/MP

The extra flat load receptor with a drive-on height of only 43 mm is designed to satisfy the highest demands when used in the foodstuff and pharmaceutical industry.



More information
High performance
with a wide range of
solutions and options.

Product description

The iL Special 4000D/MP load receptor has a simple and very flat design. It ensures low-maintenance and wear-resistant operation with a high level of long-term precision. The iL Special 4000D/MP is available built-in or freestanding, with or w/o drive-on ramps, s/s lacquered, hot-dip galvanized or made of s/s. The minimal overall height allows installation in very low pits and allows the use of short ramps. This additionally saves space when only minimal space is available at the place of installation. Thanks to a large variety of variants it is perfectly suitable for numerous applications.



iL Special 4000D/MP

Highlights

- Overall height of weighing platform only 43 mm
- Low-maintenance and wear-resistant operation
- High long-term accuracy
- 4 strain gauge load cells, hermetically sealed and corrosion-resistant
- Good shock- and vibration absorption and self-centering

Options

- Load cells in Ex ib version for Ex zone 1/21

My Bizerba

We offer you solutions from a single source which can be customized and allow you to respond to any change in a flexible manner. Benefit from costs which can be planned and efficient processes. We are happy to advise you.

Bizerba SE & Co. KG
Wilhelm-Kraut-Straße 65
72336 Balingen

T +49 7433 12-0
fax: +49 7433 12-2696
marketing@bizerba.com

www.bizerba.com