



Item	Specification	
Model		
Capacity	6kg/15kg	15kg/30kg
Readability	2g/5g	5g/10g
Divisions	2x3000e	
Housing	ABS Housing with #304 Stainless Steel Pan & Pole	
Pan Size	380x272mm	
Operator Display	4.3-inch, resolution: 480x272px	
Customer Display	IP20a: 4.3-inch, resolution: 480x272px	
	IP20b: 7-inch, resolution: 1024 x 600px	
keys	68 Tackle type membrane keys (16 functional keys, 12 Numeric Keys, 40*2 direct PLU keys)	
LAN	Support 10M/100M	
Cash box	Support 12V	
Interface	USBx1, RJ45x1, RJ11x1, RS232x1, Optional WIFI (2.4G)	
Printer	Printing Speed: Max 125mm/s	
	Paper Length: Min 20mm/Max 110mm, Paper Width: Max 60±0.5mm	
	Max Print Width: Max 56mm, Print Resolution: 203dpi	
	Printer Head Life: 50km	
	Label Types: Liner Label, Receipt	
Power	AC: 100V~240V	
Dimensions	IP20a: 400x508x177.3mm	
	IP20b: 400x508x589.3mm	
Packaging	Carton Size: 640x510x280mm, Gross weight approx. 8.5kg	
Temperature	Working: -10 °C ~ 40 °C, Storage: -20 °C ~ 60 °C	
Humidity	5%~85% R.H.	
Certification	CPA、OIML、NTEP、CE	