

## Data Sheet

Item#	Thermal Label Printing Scales	
Max Capacity	6/15KG, 15/30KG	
Verification Scale Interval	2/5g, 5/10g	
Minimum Capacity	40g, 100g	
Display	Two Line LCD 96*32 dot matrix display Weight digit : 5 digit; Unit price digit : 8digit; Total price digit : 8digit.	
Keyboard	Type:Mylar Button	
	Number :140 buttons (28 function keys , 112*2 hot keys )	
PLU Programmable Data	LFCode、Item name、Item No.、 unit price、 charge unit、 Fresh days、 Tare Weight 、 barcode、 department、 packing weight、 packing type (normal 、 fixed weight、 fixed price、 fixed weight and fixed price) 、 Info One、 Info Two、 Label format、 discount、 hotkey	
Data Storage	Store 10000PLU,can set at most 112*2 hotkeys	
Printing Speed	80mm/s	
Interface	RS232+Ethernet or RS232+Ethernet+WIFI	
Power Supply	AC100~240V,50/60Hz	
Dimension	Length437mm * Width372mm * Height523mm	
Label Paper Size	Width : 30~60mm, Maximum outer diameter : 100mm, Maximum inner Diameter : 40mm	
Paper Out Method	Tear or Strip	
Environmenta Specification	Temperture	Working : 0~40°C Storage : -20~70°C
	Humidity	Working : 20-85% Storage : 5-95%
Accuracy Class	Ⅲ	
Executive Standard	GB/T 7722-2005	