

# PLUSVAC 26

## Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

## Selectable options

- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bar
- Additional sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter

## Technical data

<b>Chamber size (w x l x h /mm)</b>	430x505x175
<b>Control board</b>	
• Standard	Comfort
• Option	Perfect
<b>Sealing length (mm)</b>	2 x 405 (4 x 405)
<b>Sealing seam</b>	double
<b>Distance x (mm)</b>	455 (400)
<b>Position of sealing bar</b>	
• Standard	front
• Option	back
<b>Pump (cbm/h)</b>	40 (60)
<b>Power connection</b>	400V/3Ph+N+PE/50Hz
<b>Power from (kW)</b>	1,5 (1,9)
<b>Max. bag (mm)</b>	400x500
<b>Insert plates</b>	2/chamber
<b>Outer dimensions (lid closed / w x d x h/mm)</b>	955x655x985
<b>Outer dimensions (lid open / w x d x h/mm)</b>	955x655x1,550
<b>Weight (kg)</b>	150 (152)

The data in brackets are options.



Picture can show options.

