

PLUSVAC 24

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Lid locking can be unhooked
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Program control with sensor (Perfect)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bars
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter
- Higher lid

Technical data

Chamber size (w x l x h / mm)	640 x 480 x 200 (250)
Control board	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	2 x 455
Sealing seam	double
Distance x (mm)	(540)
Position of sealing bar	
• Standard	right, left
• Option	right or left
Pump (cbm/h)	40 (60)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	1,5 (1,9)
Max. bag (mm)	450 x 600
Insert plates	3
Outer dimensions (lid closed / w x d x h/mm)	710 x 665 x 1,010
Outer dimensions (lid open / w x d x h/mm)	710 x 665 x 1,500
Weight (kg)	115 (117)

The data in brackets are options.

