

S 501

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Dynamic end position damping of the lid opening
- Silent ventilation
- Recessed control board
- Program control with sensor (Perfect)
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Soft ventilation
- Step/impulse vacuum
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Convex plexiglas lid

Selectable options

- Gas flushing (MAP)
- Connection for external extraction (container)
- Cut-off and sealing
- Compressed air pressure sealing, external air compressor required
- Switch off sealing bars
- Additional sealing bar
- Bigger vacuum pumps
- Voltage variants
- ESD-Version
- Plug with phase inverter

Technical data

Chamber size (w x l x h /mm)	895 x 565 x 230
Control board	
• Standard	Perfect
• Option	–
Sealing length (mm)	1 x 455 (2 x 455)+1 x 740
Sealing seam	double
Distance x (mm)	765 (480)
Position of sealing bar	
• Standard	right, front
• Option	left
Pump (cbm/h)	106 (151)
Power connection	400V/3Ph+N+PE/50Hz
Power from (kW)	3,5 (4,7)
Max. bag (mm)	450 x 800
Insert plates	4
Outer dimensions (lid closed / w x d x h/mm)	975 x 750 x 1,170
Outer dimensions (lid open / w x d x h/mm)	975 x 750 x 1,600
Weight (kg)	277 (287)

The data in brackets are options.



Picture can show options.

fmk-web.de

