

EVOLUTION 300 PRO

Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Dynamic end position damping of the lid opening
- Vacuum-moulded chambers, hygienic cleaning
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plate for height adjustment
- Convex plexiglas lid

Selectable options

- Anti-slip mat
- Cut-off and sealing
- Voltage variants
- Carts

Technical data

Chamber size (w x l x h /mm)	320 x 350 x 120
Control board	
• Standard	Comfort
• Option	–
Sealing length (mm)	1 x 305
Sealing seam	double
Distance x (mm)	290
Position of sealing bar	
• Standard	front
• Option	–
Pump (cbm/h)	8
Power connection	230V/1Ph+N+PE/50Hz
Power from (kW)	0,5
Max. bag (mm)	300 x 400
Insert plates	1
Outer dimensions (lid closed / w x d x h/mm)	370 x 400 x 305
Outer dimensions (lid open / w x d x h/mm)	370 x 400 x 600
Weight (kg)	28



Picture can show options.

fmk-web.de

