

# NIKIVAC

## Standard equipment

- Cylinder sealing
- Sealing bars are to remove without tools
- Wide double sealing
- Dynamic end position damping of the lid opening
- Silent ventilation
- Grip protection on the lid
- Recessed control board
- Robust components and construction
- Stainless steel as well as best metal alloys
- Plexiglas lid – important for packaging soups and sauces
- Service program for the pump
- Oil change indicator
- Optimised heat dissipation
- Vacuum stop button
- Microcomputer control board
- Inlet plates for height adjustment
- Flat Plexiglas lid

## Selectable options

- Program control with sensor (Perfect)
- Anti-slip mat
- Cut-off and sealing
- Voltage variants
- Carts
- Stronger sealing transformer

## Technical data

Chamber size (w x l x h /mm)	430 x 400 x 160
<b>Control board</b>	
• Standard	Comfort
• Option	Perfect
Sealing length (mm)	1 x 405
Sealing seam	double
Distance x (mm)	350
<b>Position of sealing bar</b>	
• Standard	front
• Option	–
Pump (cbm/h)	16
Power connection	230V / 1Ph+N+PE/50Hz
Power from (kW)	0,8
Max. bag (mm)	400 x 400
Insert plates	3
Outer dimensions (lid closed / w x d x h/mm)	490 x 540 x 400
Outer dimensions (lid open / w x d x h/mm)	490 x 540 x 850
Weight (kg)	57



Picture can show options.

fmk-web.de

